



## Specifications Ledvance LED Downlight DN200 35W 3150lm 100D - 865 Daylight | 215mm - IP44 - Emergency 3H

[View Product](#)

### General Information

|                          |                                    |
|--------------------------|------------------------------------|
| SKU                      | 235468                             |
| EAN                      | 4058075204362                      |
| Brand                    | Ledvance                           |
| Manufacturer Name        | DL ALU DN200 35W/6500K WT EM AT 3H |
| Any Lamp all-in warranty | 3 Years                            |
| Average Lifetime (h)     | 50000                              |

### Technical Information

|                             |                     |
|-----------------------------|---------------------|
| Emergency Lighting          | With Emergency Unit |
| Tiltable                    | No                  |
| Technology                  | LED Integrated      |
| Wattage                     | 35                  |
| Voltage (V)                 | 220-240             |
| Dimmable                    | Not Dimmable        |
| Colour Code                 | 865 Daylight        |
| Colour temperature (Kelvin) | 6500 Daylight       |
| Colour Rendering (Ra)       | 80-89               |
| Colour of Light             | White               |
| Light colour options        | Single Color        |
| Including bulb              | Yes                 |

|                          |                                       |
|--------------------------|---------------------------------------|
| Beam Angle (degree)      | 100                                   |
| Luminous Flux (Lumen)    | 3150                                  |
| Luminous Efficacy (lm/W) | 90                                    |
| Power factor             | >0.90                                 |
| Installation Depth (mm)  | 120                                   |
| Unified Glare Rating     | < 28 - for hallways and storage rooms |
| Product Type Category    | LED Downlight                         |

## Fixture Information

|                        |                   |
|------------------------|-------------------|
| Mounting Method        | Recessed          |
| Cut out (mm)           | 200               |
| IP-rating              | IP44              |
| Impact Protection (IK) | IK02 - 0.20 joule |
| Operating Temperature  | -20 to +45        |
| Housing                | Aluminium         |
| Colour of the Fixture  | White             |
| Colour of material     | White             |
| Series                 | DN205             |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 61  |
| Diameter (mm) | 215 |

## Why Any-lamp?

## Sensor Information


 Order from the **largest lighting specialist** in Europe


**Customised** quotation

Type of sensor
 


 No Sensor


 Up to **7 years warranty**


**Easy** return process