



**Specifications Philips LED Panel
SlimBlend RC400B 33.5W 3600lm - 840
Cool White | 60x60cm - UGR <19 - Dali
Dimmable**

[View Product](#)

General Information

| | |
|--------------------------|--|
| SKU | 230430 |
| EAN | 8718699174606 |
| Brand | Philips |
| Manufacturer Name | Philips SlimBlend RC400B LED36S/840 PSD W60L60 VPC W |
| Any Lamp all-in warranty | 5 Years |
| Average Lifetime (h) | 70000 |

Technical Information

| | |
|-----------------------------|--------------------|
| Technology | LED Integrated |
| Replaces (Watt) | 4x18 |
| Wattage | 33.5 |
| Voltage (V) | 220-240 |
| Dimmable | Dimmable with Dali |
| Colour Code | 840 Cool White |
| Colour temperature (Kelvin) | 4000 Cool White |
| Colour Rendering (Ra) | 80-89 |
| Colour of Light | White |
| Light colour options | Single Color |
| Luminous Flux (Lumen) | 3600 |
| Luminous Efficacy (lm/W) | 107 |

| | |
|------------------------|-------------------------------|
| Suitable for Outdoor | No |
| IP-rating | IP20 |
| Impact Protection (IK) | IK02 - 0.20 joule |
| Fixture Connection | PI [Push-in connector 3-pole] |
| Driver Included | Yes |
| Power factor | >0.95 |
| Product Type Category | LED Panel |

Fixture Information

| | |
|-----------------------|--------------------------------|
| EOC8 | 17460600 |
| Mounting Method | Recessed |
| Unified Glare Rating | < 19 - for offices and schools |
| Optical Cover | PMMA (Polymethyl methacrylate) |
| Operating Temperature | -10 to +40 |
| Emergency Lighting | No Emergency Unit |
| Colour of the Fixture | White |
| Housing | Steel |
| Colour of material | White |

Dimensions

| | |
|----------------|---------|
| LED panel size | 60x60cm |
| Length (mm) | 595 |
| Width (mm) | 595 |
| Height (mm) | 52 |

 Order from the **largest lighting specialist** in Europe  **Customised** quotation

Sensor Information  **Up to 7 years warranty**  **Easy return process**

Type of sensor No Sensor

