



**Specifications Philips LED Panel CoreLine SM136V**  
**25/34W 3100-4300lm - 840 Cool White |**  
**150x20cm - UGR <19 - Dali Dimmable - Selectable**  
**Wattage**

[View Product](#)

## General Information

|                          |                                          |
|--------------------------|------------------------------------------|
| SKU                      | 241065                                   |
| EAN                      | 8718699975555                            |
| Brand                    | Philips                                  |
| Manufacturer Name        | SM136V 31S_37S_43S/840 PSD W20L150OCELB3 |
| Any Lamp all-in warranty | 5 Years                                  |
| Average Lifetime (h)     | 50000                                    |
| Series                   | SM136V                                   |

## Technical Information

|                             |                    |
|-----------------------------|--------------------|
| Technology                  | LED Integrated     |
| Replaces (Watt)             | 2x58               |
| Wattage                     | 34                 |
| Voltage (V)                 | 220-240            |
| Dimmable                    | Dimmable with Dali |
| Colour Code                 | 840 Cool White     |
| Colour temperature (Kelvin) | 4000 Cool White    |
| Colour Rendering (Ra)       | 80-89              |
| Colour of Light             | White              |
| Light colour options        | Single Color       |
| Luminous Flux (Lumen)       | 4300               |
| Luminous Efficacy (lm/W)    | 140                |

|                        |                   |
|------------------------|-------------------|
| IP-rating              | IP20/IP44         |
| Impact Protection (IK) | IK03 - 0.35 joule |
| Fixture Connection     | Cable, 5-pole     |
| Driver Included        | Yes               |
| Power factor           | >0.90             |
| Product Type Category  | LED Panel         |

## Fixture Information

|                       |                                |
|-----------------------|--------------------------------|
| EOC8                  | 97555500                       |
| Mounting Method       | Surface                        |
| Unified Glare Rating  | < 19 - for offices and schools |
| Optical Cover         | PC (Polycarbonate)             |
| Operating Temperature | -10 to +40                     |
| Emergency Lighting    | 3H Emergency Light             |
| Colour of the Fixture | White                          |
| Housing               | Steel                          |
| Colour of material    | White                          |

## Dimensions

|                |          |
|----------------|----------|
| LED panel size | 150x20cm |
| Length (mm)    | 1430     |
| Width (mm)     | 200      |
| Height (mm)    | 68.5     |

 **Sensor Information** Order from the **largest lighting specialist** in Europe  **Customised** quotation

Type of sensor



Up to **7 years warranty**

No Sensor



**Easy** return process